MAXANT

HONEY PROCESSING EQUIPMENT

3100H 2, 6, or 9 Hand Extractor

Congratulations on purchasing the best hobbyist extractor on the market. Our company was founded on the idea of equipment that is "built to last a lifetime".

Your extractor is ready to use straight out of the box.
We recommend running warm soapy water through it while the outlet is open before its first use.
If you ordered a leg kit, assemble and bolt it to the extractor.
Your extractor is designed to hold 2, 6, or 9 frames.
You have the ability to extract 2, 6, or 9 medium frames radially, and 3 deep frames tangentially (if you have a 9 frame basket unit).

Once you have loaded your frames, slowly start spinning your extractor.
Reposition your frames if your machine is spinning off balance. Once balanced, gradually increase speed.
While extracting make sure that the outlet on the bottom is open at all times!
Do not let honey build up inside the tank!

Cleaning: When finished extracting, rinse the extractor with hot water, and let dry. **NO BLEACH OR ABRASIVE CHEMICALS.**

Annual Lubrication:
Remove the basket by taking out the two bolts that hold the center channel. Be careful not to lose the ½ inch stainless steel ball bearing that sits in the cup under the basket, when removing for maintance. Pack food grade grease and the ball back into the bearing cup after cleaning. Reassemble.

Bolts to remove center channel

58 Barnum Road, Devens MA 01434
(978). 772. 0576 / www.maxantindustries.com